

True connect 1/2" Plenum Cable



MODEL # 12/WP



FEATURES

- In-Building Systems (DAS)
- Cabling for VHF, UHF, 700, 850, PCS, & AWS Bands
- RF Cable Jumper Assemblies where low PIM is required

Construction Materials and Dimensions

Inner Conductor	Material	Copper Clad Aluminum Wire
	Diameter, in.	0.189
Dielectric	Material	PE Spline
	Diameter, in.	0.465
Outer Conductor	Material	Ring Corrugated Copper
	Diameter, in.	0.543
Jacket	Material	PVC, Plenum Rated
	Diameter, in.	0.629

Electrical Specifications

Inner conductor DC resistance, Ω /kft	0.486
Outer conductor DC resistance, Ω /kft	0.689
Impedance, Ω	50 \pm 2
Inductance, μ H/ft	0.058
Capacitance, pF/ft	23
Propogation velocity, %	88
DC breakdown voltage, kV	6.0
Insulation resistance, $M\Omega$ /km	$>5 \times 10^3$
Peak Power, kW	40
Screening attenuation, dB	$>>120$
Cut-off frequency, GHz	8.80

Mechanical Specifications

Bending radius, in.	Single	2.76
	Repeated	4.92
Tensile strength, lbs.	254	
Crush resistance, lb/in.	80	
Bending moment, ft lb.	11.4	
Storage Temperature, $^{\circ}$ F	-94 \approx +185	
Installation Temperature, $^{\circ}$ F	-40 \approx +140	
Operating Temperature, $^{\circ}$ F	-67 \approx +185	

www.wirelessupply.com

© 2019 All rights reserved. Proprietary information. Wireless Supply reserves the right to modify or amend specifications without prior notice