

Trueconnect 1/2" LOW LOSS FOAM Cable



MODEL # 12



FEATURES

- In-Building Systems (DAS)
- Cabling for VHF, UHF, 700, 850, PCS, & AWS Bands
- RF Cable Jumper Assemblies where low PIM is required

Construction Materials and Dimensions

	Material	
Inner Conductor	Copper Clad Aluminum Wire	
	Diameter, in.	0.189
Dielectric	Physically foamed PE	
	Diameter, in.	0.480
Outer Conductor	Helical Corrugated Copper	
	Diameter, in.	0.543
Jacket	PE	
	Diameter, in.	0.622

Electrical Specifications

Inner conductor DC resistance, Ω /kft	0.450
Outer conductor DC resistance, Ω /kft	0.820
Impedance, Ω	50 \pm 2
Inductance, μ H/ft	0.19
Capacitance, pF/ft	23.1
Propogations velocity, %	88
DC breakdown voltage, kV	4.0
Insulation resistance, M Ω km	>5X10 ³
Peak Power, kW	40
Screening attenuation, dB	>> 120
Cut-off frequency, GHz	8.80

Mechanical Specifications

Bending radius, in.	Single	2.00
	Repeated	5.00
Tensile strength, lbs.		250
Crush resistance, lb/in.		110
Bending moment, ft lb.		2.8
Storage Temperature, °F		-94 \approx +185
Installation Temperature, °F		-40 \approx +140
Operating Temperature, °F		-67 \approx +185

Trueconnect 1/2" LOW LOSS FOAM CABLE



MODEL # 12

Attenuation		
Frequency	dB/100 ft	dB/100 m
10	0.20	0.67
100	0.66	2.17
200	0.95	3.10
450	1.45	4.75
800	1.97	6.46
900	2.09	6.85
1000	2.22	7.28
1500	2.77	9.09
1800	3.08	10.10
2000	3.26	10.70
2300	3.52	11.54
3000	4.08	13.40
6000	6.11	20.05



VSWR		
806-960 MHz		≤1.15
1700-2400 MHz		≤1.15
5-3000 MHz		≤1.25

Available Connectors	
Connector Type	Connector Part Number
NM	12-NM
NF	12-NF
7/16 DIN M	12-DM
7/16 DIN F	12-DF
4.1/9.5 Male	12-41M
4.1/9.5 Female	12-41F
4.3/10 Male	12-43M
4.3/10 Female	12-43F



www.wirelessupply.com

© 2019 All rights reserved. Proprietary information. Wireless Supply reserves the right to modify or amend specifications without prior notice