

Trueconnect 3/8" SUPERFLEXIBLE CABLE



MODEL # 38/SF



FEATURES

- In-Building Systems (DAS)
- Cabling for VHF, UHF, 700, 850, PCS, & AWS Bands
- RF Cable Jumper Assemblies where low PIM is required

Construction Materials and Dimensions

Inner Conductor	Material	Copper Clad Aluminum Wire
	Diameter, in.	0.110
Dielectric	Material	Physically foamed PE
	Diameter, in.	0.276
Outer Conductor	Material	Helical Corrugated Copper
	Diameter, in.	0.375
Jacket	Material	PE
	Diameter, in.	0.425

Electrical Specifications

Inner conductor DC resistance, Ω /kft	1.290
Outer conductor DC resistance, Ω /kft	1.520
Impedance, Ω	50 \pm 2
Inductance, μ H/ft	0.061
Capacitance, pF/ft	24.3
Propogations velocity, %	81
DC breakdown voltage, kV	2.5
Insulation resistance, M Ω km	>5X10 ³
Peak Power, kW	13.2
Screening attenuation, dB	>> 120
Cut-off frequency, GHz	10.20

Mechanical Specifications

Bending radius, in.	Single	1.00
	Repeated	2.00
Tensile strength, lbs.		210
Crush resistance, lb/in.		100
Bending moment, ft lb.		1.7
Storage Temperature, °F		-94 \approx +185
Installation Temperature, °F		-40 \approx +140
Operating Temperature, °F		-67 \approx +185

www.wirelessupply.com

© 2019 All rights reserved. Proprietary information. Wireless Supply reserves the right to modify or amend specifications without prior notice

Trueconnect 3/8" SUPERFLEXIBLE CABLE



MODEL # 38/SF

Attenuation		
Frequency	dB/100 ft	dB/100 m
10	0.37	1.22
100	1.20	3.94
200	1.72	5.65
450	2.64	8.66
800	3.60	11.80
900	3.81	12.50
1000	4.05	13.30
1500	5.08	16.68
1800	5.64	18.50
2000	5.97	19.60
2300	6.30	20.68
3000	7.53	24.70
6000	11.32	37.15



VSWR		
806-960 MHz		≤1.15
1700-2400 MHz		≤1.15
5-3000 MHz		≤1.25

Available Connectors	
Connector Type	Connector Part Number
NM	38S-NM
NF	38S-NF
7/16 DIN M	38S-DM
7/16 DIN F	38S-DF
4.1/9.5 Male	38S-41M
4.1/9.5 Female	38S-41F
4.3/10 Male	38S-43M
4.3/10 Female	38S-43F



www.wirelessupply.com

© 2019 All rights reserved. Proprietary information. Wireless Supply reserves the right to modify or amend specifications without prior notice