

# Trueconnect™ 4-WAY LOW POWER SPLITTER



**MODEL - 4WPSWB/43**



Low PIM 4-Way Power Splitter  
[600-6000 MHz]

## FEATURES

Wilkinson design Wide Band power splitter that offers optimal performance and low PIM specifications.

## Specifications

Frequency Range (MHz)	600-6000
PIM, 3rd Order (dBc)	-153
PIM Test Method	2 X +43 dBm carriers
Power Rating, Combining (W)	1
Power Rating, Splitting (W)	50
Peak Power (kW)	1
Impedance (Ω)	50
Insertion Loss (dB)	2.8
Isolation @ Frequency (dB)	
	698-800 16
	800-2500 16
	2500-2700 16
VSWR	≤1.50:1
Split Loss (dB)	6
Connector	4.3-10 Female
Application	Indoor/Outdoor
Ingress Test Method	IEC 60529:2001 IP65
Operating temperature - °F (°C)	-13 to 185 (-25 to 85)
Relative Humidity	up to 100%
Dimensions in. (mm)	4.45 X 3.94 X 1.14 (121 X 108 X 29)
Weight lbs (kg)	1.43 (.65)

[www.wirelessupply.com](http://www.wirelessupply.com)

© 2019 All rights reserved. Proprietary information. Wireless Supply reserves the right to modify or amend specifications without prior notice