

# True connect DIRECTIONAL COUPLER WIDEBAND



**MODEL # 15DCWB/43**




## FEATURES

Typically used in In-building DAS systems to provide coverage solutions for 600 Band, 700PS, 700 LTE, 800PS, 850 CELL, PCS, AWS, WCS, 2.5 band, CBRS Band, 5 & 6 GHz

- Low PIM
- Low Insertion Loss
- High Power

## Specifications

|  |   |
|--|---|
| Frequency Range (MHz)                        | 600-6000  |
| Connector                                    | 4.3/10 Female                                   |
| Coupling (dB)                                | 15  |
| Coupling Tolerance (dB)                      | ±1.2  |
| PIM, 3 <sup>rd</sup> order @ 2 X 43 dBm(dBc) | ≤-161 (602-2700)                                |
| Impedance                                    | 50Ω   |
| Insertion Loss (dB)                          | ≤0.4  |
| Isolation (dB)                               | ≥35   |
| VSWR/Return Loss                             | ≤1.4 (600-698) ≤1.3 (698-2700) ≤1.5 (2700-6000) |
| Max Power Input (W)                          | 200   |
| Peak Power (kW)                              | 1.5   |
| Dimensions in. (mm)                          | 5.04 X 1.85 X 1.14 (128 X 47 X 29)              |
| Operating Temperature °F (°C)                | -22 to 150 (-30 to 65)                          |
| Weight (lbs)                                 | 1.15  |



[www.wirelessupply.com](http://www.wirelessupply.com)

© 2019 All rights reserved. Proprietary information. Wireless Supply reserves the right to modify or amend specifications without prior notice