

True connect 1/2" Plenum cable



WIRELESS SUPPLY
HIGHER STANDARDS. SUPERIOR QUALITY.

MODEL # 12/WP



FEATURES

- In-Building Systems (DAS)
- Cabling for VHF, UHF, 700, 850, PCS, AWS, CBRS C Band, 4G and 5G systems
- RF Cable Jumper Assemblies where low PIM is required

Construction Materials and Dimensions

Inner Conductor	Material	Copper Clad Aluminum Wire
	Diameter, in.	0.189
Dielectric	Material	PE Spline
	Diameter, in.	0.465
Outer Conductor	Material	Ring Corrugated Copper
	Diameter, in.	0.543
Jacket	Material	PVC, Plenum Rated
	Diameter, in.	0.629

Electrical Specifications

Inner conductor DC resistance, Ω /kft	0.486
Outer conductor DC resistance, Ω /kft	0.689
Impedance, Ω	50 \pm 2
Inductance, μ H/ft	0.058
Capacitance, pF/ft	23
Propagation velocity, %	88
DC breakdown voltage, kV	6.0
Insulation resistance, M Ω /km	>5X10 ³
Peak Power, kW	40
Screening attenuation, dB	>>120
Cut-off frequency, GHz	8.80

Mechanical Specifications

Bending radius, in.	Single	2.76
	Repeated	4.92
Tensile strength, lbs.		254
Crush resistance, lb/in.		80
Bending moment, ft lb.		11.4
Storage Temperature, °F		-94 \approx +185
Installation Temperature, °F		-40 \approx +140
Operating Temperature, °F		-67 \approx +185

Attenuation

Frequency	dB/100 ft	dB/100 m
10	0.21	0.67
100	0.67	2.19
200	0.96	3.15
450	1.48	4.85
750	1.96	6.43
850	2.09	6.86
900	2.15	7.07
1000	2.30	7.53
1500	2.88	9.46
1700	3.10	10.17
1800	3.20	10.50
2000	3.40	11.16
2200	3.60	11.81
2300	3.69	12.11
2700	4.08	13.39
3000	4.36	14.16
3400	4.69	15.39
3700	4.93	16.18
4000	5.16	16.93
4200	5.31	17.43
5000	5.89	19.33
6000	6.58	21.58

VSWR

600-2400 MHz	\leq 1.07
2400-4200 MHz	\leq 1.15
5100-6000 MHz	\leq 1.17

Fire Retardant Properties

ETL Listed to UL 444, Canadian CSA
C.22.2/FT6 CATV/CMP, NFPA-262



www.wirelessupply.com

© 2019 All rights reserved. Proprietary information. Wireless Supply reserves the right to modify or amend specifications without prior notice