# Truepath PUBLIC SAFETY BDA 700 and 800 MHZ 2W-GLASS A AC



- Compact, high performance, economical public safety signal source
- UL2524 Certified UL File \$36319
- High performance digital programmable architecture supports up to 32 channels per band
- Automatic Gain Control (AGC) and channelized uplink squelch ensure clear voice transmission
- Output power and band capacity can be field upgradeable via license key
- Web-based GUI and SNMP support for intelligent configuration and monitoring
- NFPA 1225 and IFC complaint
- Built-in automatic donor antenna supervision

4.3-10 female

- Automatic oscillation detection and self-healing mechanism
- Short installation time due to built-in isolation test, alarm test and one click summary report

#### **GENERAL SPECIFICATIONS**

Antenna Interface at Repeater Supervision/Control Option

#### **DIMENSIONS**

 Height
 480 mm | 18.898 in

 Width
 400 mm | 15.748 in

 Depth
 170 mm | 6.693 in

#### **ELECTRICAL SPECIFICATIONS**

Electrical Safety Standard

Gain, typical
Gain Adjustment Range
Group Delay, maximum, specfic
License Band
Local Power
Mains Power
Return Loss

Power Consumption

## CAN/CSA-C22.2 No. 62368-1 | UL 2524 Certified | UL 62638 | US FCC Part 20

Dry Alarm contacts with 2.2K Ohm EOL resistors | Remote control via Ethernet

US FCC Part 90

90 dB 30 dB

3 μs @ full band | 90 μs @ 12.5 kHz 700 (including FirstNet) | 800

110 VAC

110VAC/60 Hz

13 dB 160W

#### ELECTRICAL SPECIFICATIONS, Rx (Uplink)

Operating Frequency Band Output Power @ One Carrier Output Power @ Two Carriers 788-798 MHz (FirstNet) | 788-805 MHz | 796-824 MHz

27 dBm 24 dBm

### ELECTRICAL SPECIFICATIONS, Tx (Downlink)

Operating Frequency Band Output Power @ One Carrier 758-768 MHz (FirstNet) | 758-775 MHz | 851-896 MHz

33 dBm

19 kg | 41.888 lb

www.wirelesssupply.com