

480 mm | 18.898 in 400 mm | 15.748 in 170 mm | 6.693 in

### DIMENSIONS

Height	
Width	
Depth	

## ELECTRICAL SPECIFICATIONS

**Electrical Safety Standard** 

Gain, typical Gain Adjustment Range Group Delay, maximum, specfic License Band Local Power Return Loss Power Consumption

#### ELECTRICAL SPECIFICATIONS, Rx (Uplink)

Operating Frequency Band Output Power @ One Carrier Output Power @ Two Carriers

### ELECTRICAL SPECIFICATIONS, Tx (Downlink)

Operating Frequency Band Output Power @ One Carrier Output Power @ Two Carriers CAN/CSA-C22.2 No. 62368-1 | UL 2524 Certified | UL 62638 | US FCC Part 20 US FCC Part 90 90 dB 30 dB 3 µs @ full band | 90 µs @ 12.5 kHz 700 (including FirstNet) | 800 -48 Vdc 13 dB 160W

788-798 MHz (FirstNet) | 788-805 MHz | 796-824 MHz 27 dBm 24 dBm

758-768 MHz (FirstNet) | 758-775 MHz | 851-896 MHz 27 dBm 24 dBm

## 19 kg | 41.888 lb

# www.wirelesssupply.com

© 2019 All rights reserved. Proprietary information. Wireless Supply reserves the right to modify or amend specifications without prior notice